

HOFMANN®



monty™ 3300/3300em

TIRE CHANGER

monty™ 3300/3300em

The Hofmann monty 3300 and 3300em high-performance tire changers are designed for high-volume tire shops, multi-bay repair shops and car dealerships. Technicians can effortlessly & safely change standard tires or the most difficult performance tires (low-profile and run-flat tires) on cars, SUV's and light trucks. The monty 3300 series features a powerful, multi-position bead breaker that delivers 6,000 lbs. of power at the bead shovel, making easy jobs of both the stiffest and softest sidewalls.

Accommodates Large Wheel & Tire Assemblies

Allowing for a tire diameter of 40" and an outer-wheel clamping diameter of 24", the monty 3300/3300em can handle wheel and tire assemblies found on cars and light trucks.

Dual Wheel Clamping Cylinders

Dual pneumatic clamping cylinders control all four clamping jaws, eliminating damage to wheels due to slippage.

Multi-Position Bead Breaker

6,000 lbs. of power at the bead shovel and a range of up to 17" wide. The two-stage pneumatic cylinder provides precise power and can be toggled with the foot pedal as needed. Both the stiffest and the softest sidewalls are a snap. No damage to tires while loosening the beads!

Powerful Tire Inflation System

Powerful air blast operated by the foot pedal. Each moveable jaw is precisely set to the exact position under the wheel to seal the tire bead.

Built To Last

Heavy, solid 1/2" thick steel clamping table. Rugged steel-reinforced chassis. Rust-proof air cylinders and valves. Compressed air lubricator and regulator on-board - keeps valves and cylinders maintenance-free!

Upgradeable

EasyMont Pro* features a three-piece design with a Top Roller, Pressing Foot, and Lifting Disc. Each piece provides a specialized function that assists a single operator in mounting/demounting low-profile and high-performance tires.

* Standard with monty 3300em, optional for monty 3300

TIRE CHANGER

Specifications

Overall Wheel Clamping Diameter:	10" - 24"
Inner-Wheel Clamping Diameter:	12" - 24"
Outer-Wheel Clamping Diameter:	10" - 24"
Bead Breaker Range:	2" - 17"
Bead Loosening Power:	6,000 lbs.
Maximum Wheel Width:	15"
Maximum Outer Tire Diameter:	40"
Shipping Weight:	855 lbs. (monty 3300em) 625 lbs. (monty 3300)
Power Requirements*:	120V, 1Ph, 60Hz

Drive Motor/Air Supply Options

Electric (standard)	1HP
Air (optional)	Available on request, 110 - 175 psi @ 5 CFM

Optional Accessories

EAA0329G35A	EasyMont Pro bead assist device*
EAA0329G53A	Motorcycle/ATV adapters (8" - 24" outer clamping diameter)
4028228	Quick change bead head kit*
EAA0247G20A	Composite mount/demount head
EAA0247G04A	Protective cover* (for tire lever)
ST4027645	Outside clamping jaw protectors (4 each)
ST0022129	Snap-in jaw protector
EAA0304G15A	Protective cover for bead breaker shovel*
ST4026853	Rim protector, snaps onto rim of wheel* (3 each - use with wave tire tool)
EAA0247G15A	Protective insert for mount/demount head (10 each)
ST0024335	Replacement composite head
EAA0304G14A	Wave tire tool
ST4028648	Magic bead pusher (use with EasyMont)
EAA0329G92A	Hex bar with roller attachment (Use with EasyMont)
EAA0304G43A	Bead breaker disc (Use with hex bar)
EAA0247G70A	Bead clamp for performance wheels
ST4024078	Bead clamp for run-flat tires
ST0029455	Protective slide cover
1970995	Premium tire paste

* Accessories come standard with monty 3300em



309 Exchange Avenue • Conway, AR 72032
(800) 251-4500 • (501) 505-2662
Fax (501) 450-2085 • www.hofmann-usa.com



6500 Millcreek Drive • Mississauga, ONT L5N 2W6
(800) 267-2185
Fax (905) 821-2073 • www.hofmann.ca